

HIGHLIGHTS

- · Rotax® V-Twin engine
- Arched double A-arm front suspension with front sway bar
- 28 in. ITP† Mega Mayhem† tires
- 12 in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok[†] QE auto-locking front differential
- · Relocated radiator
- · Heavy-duty front bumper
- Mud-riding footrests
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing-Arm Independent (TTI) rear suspension
- 625 W magneto
- · X-package coloration, graphics and seat cover
- Mudguards



Granite Gray, Black & Manta Green / 650

ENGINE	650
Туре	62 hp, Rotax 649.6 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P/R/N/H/L, standard engine braking
Drive Train	Selectable 2WD/4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar

303F EN310143	
Front Suspension	Arched double A-arm with front sway bar
Front Shocks	Oil
Rear Suspension	Torsional Trailing-Arm Independent (TTI)
Rear Shocks	Oil

TIRES	&	w	Н	Е	E	LS

Front Tires	ITP Mega Mayhem [‡] 28 x 8 x 12 in. (71.1 x 20.3 x 30.5 cm)
Rear Tires	ITP Mega Mayhem [‡] 28 x 10 x 12 in. (71.1 x 25.4 x 30.5 cm)
Wheels	12 in. cast-aluminum

В	R	A	K	E	S	

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

DIMENSIONS & CAPACITIES

Estimated Dry Weight*	874 lb (396 kg)	
LxWxH	88 x 48.5 x 50.5 in. (224 x 123 x 128 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	11.75 in. (29.9 cm)	
Seat Height	35.25 in. (89.5 cm)	
Rack Capacity	Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,650 lb (750 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES

Gauge	4.5 in. digital display: Speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock
Instrumentation	Lighter type DC outlet in console, standard connector in the back (15 A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light
Winch	Prewired for available winch
Seat	Standard
Protection	Heavy-duty front bumper Mud-riding footrests Mudguards

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

